



MILES Target

Key Features:

- 7 MILES Sensors for flawless performance
- Sense “Kill” signal and send “die” command target system
- For use with MT Series robotic targets, PT Series pop-up lifters and/or turning target systems
- Powered by target system, so no additional hardware is needed.

Boost your virtual training to day by integrating MILES targets into your training curriculum without the need for additional special targetry.

MILES SPECIFICATIONS

DIMENSIONS	
Base	Standard ARMY-E Silhouette
WEIGHT	
Base	12 lbs.
ENVIRONMENTAL	
Temperature	32°F to 140°F (0°C TO 60°C)
Rain	Water resistant, do not submerge
BATTERY	
Type	Powered by target system (12VDC)
Connector (Data and power)	Amphenol Mil Spec
MILES	
Sensors	7 sensors for optimal performance
Type	Advanced Legacy MILES Generation 1 MCC-PMT-90-S200M
Functions	<p>Kill signal from MILES will send “die” signal to lifter. This results in either “die” or “bob” action.</p> <p>Target can send Reset signal to MILES sensors based upon Friend/Edge/or Foe command received by target from controller</p>

WHAT’S IN THE BOX:

- MILES Target
- ATS Targets Adapter Dongle

KEY ACCESSORIES TO CONSIDER:

- PT-61A Fully programmable pop-up or pop-up turning target
- MT Series all terrain robotic target platform
- GPS Options